


## Performa™ 71041112/ 71041122

Performa™ AFD, Series 7104, 60" x 29" Bath - Right- hand (71041122)/ Left-hand (71041112) Drain

Product Group  
Vikrell Sanitary Ware



### Product Specifications

Packaged Product Weight (kg)	40.1
Product Recycled Content	0%
Product Recyclable Content	43%
Product Life time (years)	20
Product Application	Residential

### Use Phase Specifications

Flush Volume (gal/ flush)	N/A
User Frequency (flushes/day/person)	N/A
Annual Cleaing Frequency (times)	52
Cleaner	50 ml of 1% sodium lauryl sulfate

### Greenhouse Gas Emission (kg CO2- eq.)

Material & Manufacturing	72
Use & Maintenance	10

### Water Intensity (m3)

Material & Manufacturing	37.22
Use & Maintenance	3.27

### Manufacturing Locations

Huntsville, Al

## Believing in Better

We believe in a better world. We are passionate about protecting the environment and enhancing the quality of life for current and future generations. And that means designing products that look beautiful and deliver exceptional performance, while being as sustainable as possible.



# Environmental Product Declaration

Vikrell Sanitary Ware



Program Operator Name, Address, Logo, and Website	UL Environment
General Program Instructions and Version Number	Program Operator Rules V2.3 February 2018
Location of Explanatory Material	Huntsville, AL
Declaration Holder and Address	Kohler Co. 444 Highland Drive, Kohler, WI
Declaration Number	4788111728.107.1
Declared Product and Functional Unit	Performa™ 71041112/ 71041122, Single Tub
Product Definition	Performa™ AFD, Series 7104, 60" x 29" Bath - Right- hand (71041122)/ Left-hand (71041112) Drain
Reference PCR and Version Number	PCR for Building-Related Products and Services. Adapted for UL Environment from the range of Environmental Product Declarations of Institute Construction and Environment e.V. (IBU). Part A (v.3): Calculation Rules for the Life Cycle Assessment and Requirements on the Project Report. Part B (v.1): Plumbing Vessel EPD Requirements
Markets of Applicability	North America
Date of Issue	04-Jun-18
Period of Validity	5 Years
EPD Type	Product Specific
EPD Scope	Cradle-to-grave
Year of Reported Manufacturer Primary Data	2016
LCA Software and Version Number	SimaPro v. 8.4.0.0
LCIA Database(s) and Version Numbers	Ecoinvent 3 DATASMART LCI Package (USEI 2.2)
LCIA Methodology and Version Number	TRACI 2.1 v1.04 CML-IA baseline v3.04 Cumulative Energy Demand (CED) v1.09
Applicable Green Building Certifications Schema	LEED v4/BD+C/Materials and Resources/Building Product Disclosure and Optimization- Environmental Product Declarations

# Environmental Product Declaration

Vikrell Sanitary Ware



The PCR review was conducted by:

This declaration was independently verified in accordance with ISO 14025:2006. The UL Environment "Part A: calculation Rules for the Life Cycle Assessment Reuirements on the Project Report" v3.0 (December 2017), based on CEN Norm EN 15804 (2012) and ISO 21930:2017, serves as the core PCR, with additional considerations from the USGBC/ UL Environment Part A Enhancement (2017).

INTERNAL

EXTERNAL

This life cycle assessment was conducted in accordance with ISO 14044 and reference PCR by:


This life cycle assessment was independently verified in accordance with ISO 14044 and the reference PCR by:

Thomas Gloria, Life-Cycle Services, LLC


LIMITATIONS: 1) Environmnetal declarations from different programs (ISO 14025) may not be comparable; 2) Comparison of the environmnetal performance using EPD information shall be based on the prodcut's use and impacts at the building level, and therefore EPDs may not be used for comparability purposes when not considering the building use phase as instructed under this PCR; 3) Full conformance with the PCR allows EPD comparability when all stages of a life cycle have been considered, when they comply with all referenced standards, use the same sub-category PCR, and use equivalent scenarios with respect to constrution work. However, variations and deviations are possible. example of variations: Different LCA software and background LCI datasets may lead to differences results for upstream or downstream of the life cycle stages declared.

This document is an environmental product declaration (EPD) in accordance with ISO 21930. EPDs rely on Life Cycle Assessment (LCA) to provide information on a number of environmental impacts of products over their life cycles.

At Kohler Co., we believe in protecting the environment and enhancing the quality of life for current and future generations. When developing new products, we consider the environmental impact at each stage of a product's existence - from the activities of our suppliers through the end of the product's useful life. Designing for a better world means every choice counts.



## Product Description



The clean, pared-down design of Performa(TM) by Sterling, made of solid Vikrell® material, provides a relaxing, spacious bath that easily blends with a variety of decor. The high gloss finish provides a shiny look that is easy to clean.

Additional data can be found at:

[Product Webpage](#)

## Applications and Uses

- Durable high gloss finish
- Above-floor-drain (AFD) rough-in
- 17-1/4" (438 mm) bath depth (floor to top of threshold)
- 60" (1524 mm) x 29 " (737 mm) x 17-1/4" (438 mm) complete unit finished dimension

## Product Standards, Approvals and Certifications

Specified model meets or exceeds the following:

- CSA B45.5/IAPMO Z124
- Greenguard UL 2818
- ADA Compliant
- ICC/ANSI A117.1
- ASTM E162

## SUPPLIER OPERATIONS

### Base Material Content of the Product

Material	Function	Quantity (% By Weight)
Calcium carbonate	SMC Ingredient	57-69
Polyester Resin	SMC Ingredient	15-23
Glass	SMC Additive Ingredient	7-17
Balance	Miscellaneous Hardware and Packaging	1-21

## KOHLER OPERATIONS


### Manufacturing Process Description

Vikrell products are created using a glass reinforced composite material made from polystyrene, polyester, and other additives. The correct amount of material needed for the product is weighed, and the hydraulic presses and heated molds form it into the proper shape. Once removed from the press, any excess material is trimmed, and the final product is inspected, packaged, and shipped.

### Manufacturing Locations



### Manufacturing Process



### Health, Safety and Environmental Aspects during Production

Kohler Co. has established program management guidelines for safety, accident prevention and environmental performance. These systems enable Kohler Co. operations to achieve world-class performance: Kohler Safety Management System (KSMS) and Kohler Environmental Management System (KEMS). The management systems are based on best management practices, and the application of these programs consistently delivers significant results.

### Packaging

Vikrell is packaged primarily with kraft single-wall corrugated containerboard. Other packaging material can include expanded polystyrene (EPS), co-polymer foam made up of 70% expanded polystyrene (EPS) and 30% expanded polyethylene (EPE) and honeycomb paperboard blocking. Other less common packaging material utilized is kraft double-wall corrugated containerboard, expanded polystyrene (EPS) with a pressure sensitive adhesive (PSA) and low-density polyethylene bags (LDPE). Corrugated containerboard and honeycomb blocking are 100% recyclable, and collection is available in most municipalities. Other materials are typically recyclable; however, this is dependent on local availability of collection programs.



### Conditions of Use

The majority of product use phase environmental impacts for acrylic ware are related to water throughput. It is important to note that water use impacts are assigned to the device that controls water flow rate. For example, a bathtub EPD will not include these impacts, as water consumption is controlled by the faucet that is paired with it. Similarly, a toilet bowl EPD will not include water use impacts, as the tank or flushometer it is paired with provides this function. However, a one-piece toilet with integrated tank and bowl will include water use impacts within its EPD.

### Reference Service Life

Residential bathtubs are assumed to remain in service for 20 years.

### Cleaning and Maintenance

Residential bathtubs are assumed to require 52 cleanings per year with 50 ml of 1% sodium lauryl sulfate. These impacts are included within the product use stage of the LCA.



### Recycle or Reuse

Collection and processing for SMC products are not available at present time and these products are usually landfilled.

### Disposal

Upon PCR default assumptions, The KOHLER® LCA model assumes 100% of the vikrell portion of the product, accessories and packaging materials are landfilled.

## LIFE CYCLE ASSESSMENT

### Description of Declared or Functional Unit

The functional unit represented here refers to a single bathtub.

Name	Value	Unit
Functional Unit	1 packaged product piece	
Mass	40.11	kg
Conversion factor to 1 kg	0.02	
Flush rate	0	m3/flush
Flow rate	-	m3/sec

### Estimates and Assumptions

The LCI/ LCA assumptions are mentioned below:

- Product transport from DC to final customer and from customer to disposal site are modeled based on PCR specifications
- Product and packaging disposal scenarios are adopted from the PCR specifications
- Building estimated service life (ESL) is assumed to be 75 years
- Biogenic carbon removal is estimated for two types of packaging materials including corrugate box and kraft papers

### Cut-off Criteria

This LCA is in compliance with the cutoff criteria specified in the PCR, as no known processes were excluded from this assessment outside of the specific items listed within the “System Boundary” section below.

### Allocation

Impacts are allocated to individual products with a unit process approach. Typically, product mass is used to build the impact allocation factors. Product-specific quality data is also employed to match impacts to products.

### Data Sources

Primary manufacturing data was collected directly from process experts for the one Kohler vikrell plant within North America, for the calendar year of 2016. Secondary data primarily references the DATSMART LCI database. This database is widely distributed and is referenced within the LCA community. All ecoinvent datasets have been critically reviewed.

### Data Quality

Wherever secondary data is used, the study adopts critically reviewed data for consistency, precision and reproducibility to limit uncertainty. The data sources used are complete and representative of North America in terms of the geographic and technological coverage and are a recent vintage (i.e., less than ten years old). Any deviations from these initial data quality requirements for secondary data are documented in the critically reviewed LCA report.

LCA Modeling Scenarios

Transport from gate to the building site (A4)		
Name	Value	Unit
Liters of fuel	38	l/100 km
Transport distance	821.9	km
Capacity utilization (including empty runs)	89	%
Gross density of products transported	-	kg/m <sup>3</sup>
Capacity utilization volume factor	89	-

Installation into the building (A5)		
Name	Value	Unit
Auxiliary material	-	kg
Water consumption	-	m <sup>3</sup>
Other resources	-	km
Electricity consumption	-	kWh
Other energy carriers	-	MJ
Product loss per functional unit	-	kg
Waste material at the construction site before waste processing	37.62	kg
Output materials resulting from on-site waste processing	-	kg
Direct emissions to ambient air, soil and water	-	kg

Reference service life		
Name	Value	Unit
Reference service life (RSL)	20	years

Maintenance (B2)		
Name	Value	Unit
Maintenance process information	-	-
Maintenance cycle	1040	Number/RSL
Maintenance cycle	3900	Number/ESL
Water consumption	-	m <sup>3</sup>
Auxiliary material (cleaning agent)	23.59	kg
Other resources	-	kg
Electricity consumption	-	kWh
Other energy carriers	-	MJ
Power output of equipment	-	kW
Material loss	-	kg
Direct emissions to ambient air, soil and water	-	kg

Repair (B3)		
Name	Value	Unit
Repair process information	-	-
Inspection process information	-	-
Repair cycle	-	Number/RSL
Repair cycle	-	Number/ ESL
Water consumption	-	m <sup>3</sup>
Auxiliary	-	kg
Other resources	-	kg
Electricity consumption	-	kWh
Other energy carriers	-	MJ
Material loss	-	kg
Direct emissions to air, soil and water	-	kg

Replacement (B4)/Refurbishment (B5)		
Name	Value	Unit
Replacement cycle	1	Number/RSL
Replacement cycle	2.75	Number/ESL
Electricity consumption	-	kWh
Liters of fuel	104.5	l/100 km
Water consumption	-	m <sup>3</sup>
Auxiliary material	-	kg
Replacement of worn parts	-	kg
Direct emissions to air, soil and water	-	kg

Operational energy use (B6) and water use (B7)		
Name	Value	Unit
Water consumption	-	m <sup>3</sup> /p/RSL
Electricity consumption	-	kWh
Other energy carriers	-	MJ
Equipment output	-	kW
Direct emissions to air, soil and water	-	kg

End of life (C1-C4)		
Name	Value	Unit
Collected separately	17.07	kg
Collected as mixed construction waste	24.49	kg
Reuse	-	kg
Recycling	-	kg
Energy recovery	-	kg
Landfilling	41.56	kg



### System Boundaries

	Product Stage			Construction Process Stage		Use Stage							End of Life Stage				Benefits and Loads Beyond the System Boundaries	Reference Service Life
	Raw material supply	Transport	Manufacturing	Transport from gate to the site	Assembly/ Install	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling potential	
Cradle to grave with options	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D	
	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	MND

Description of the System Boundary Stages Corresponding to the PCR  
(X = Included; MND = Module Not Declared)

### Results of the Assessment

TRACI 2.1 Impact Assessment						
Module	GWP	ODP	AP	EP	POCP	ADP
	(kg CO2 Eq.)	(kg CFC-11 Eq.)	(kg SO2- Eq.)	(kg N-Eq.)	(kg O3-Eq.)	(MJ surplus)
Total	8.35E+01	5.59E-06	3.35E-01	1.45E-01	5.02E+00	1.61E+02
A1- A3	7.22E+01	5.17E-06	2.78E-01	1.13E-01	3.84E+00	1.46E+02
A4	3.87E+00	5.09E-08	2.24E-02	2.21E-03	6.54E-01	7.30E+00
A5	5.29E-02	1.10E-08	2.28E-04	3.11E-03	6.31E-03	1.10E-01
B1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B2	6.56E+00	2.56E-07	2.96E-02	2.60E-02	3.81E-01	5.89E+00
B3	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B5	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B6	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B7	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C2	4.45E-01	7.81E-10	2.58E-03	2.41E-04	7.52E-02	8.34E-01
C3	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C4	3.35E-01	1.00E-07	2.30E-03	6.91E-04	6.22E-02	1.05E+00

CML 4.1 Impact Assessment							
Module	GWP	ODP	AP Air	EP	POCP	ADP element	ADP fossil fuels
	(kg CO2-Eq.)	(kg CFC-11 Eq.)	(kg SO2-Eq.)	(kg (PO4)3- Eq.)	(kg C2H4 Eq.)	(kg Sb-Eq.)	(MJ, LHV)
Total	8.44E+01	4.71E-06	3.23E-01	8.89E-02	2.77E-02	1.10E-04	1.28E+03
A1- A3	7.31E+01	4.39E-06	2.74E-01	6.85E-02	1.64E-02	8.87E-05	1.16E+03
A4	3.90E+00	3.73E-08	1.80E-02	3.85E-03	7.32E-04	6.98E-07	5.18E+01
A5	5.67E-02	8.23E-09	1.85E-04	1.15E-03	1.10E-05	3.41E-08	7.92E-01
B1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B2	6.60E+00	1.90E-07	2.70E-02	1.44E-02	1.04E-02	2.07E-05	5.16E+01
B3	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B5	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B6	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B7	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C2	4.48E-01	4.89E-10	2.06E-03	4.38E-04	8.51E-05	2.02E-08	5.90E+00
C3	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C4	3.40E-01	7.50E-08	1.89E-03	5.55E-04	7.27E-05	3.72E-07	7.70E+00

Rest of the World Impact Assessment					
Module	GWP	ODP	AP	EP	POCP
	(kg CO2-Eq.)	(kg CFC-11 Eq.)	(kg SO2-Eq.)	(kg N-Eq.)	(kg O3- Eq.)
Total	8.44E+01	4.71E-06	3.23E-01	8.84E-02	5.02E+00
A1- A3	7.31E+01	4.39E-06	2.74E-01	6.85E-02	3.84E+00
A4	3.90E+00	3.73E-08	1.80E-02	3.85E-03	6.54E-01
A5	5.67E-02	8.23E-09	1.85E-04	1.15E-03	6.31E-03
B1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B2	6.60E+00	1.90E-07	2.70E-02	1.44E-02	3.81E-01
B3	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B5	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B6	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B7	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C2	4.48E-01	4.89E-10	2.06E-03	4.38E-04	7.52E-02
C3	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C4	3.40E-01	7.50E-08	1.89E-03	0.00E+00	6.22E-02

# Environmental Product Declaration

Vikrell Sanitary Ware



Resource Use											
Module	RPRe	PRPm	RPRt	NRPRe	NPRPm	NRPRt	SM	RSF	NRSF	RE	FW
	(MJ)	(MJ)	(MJ)	(MJ)	(MJ)	(MJ)	(kg)	(MJ)	(MJ)	(MJ)	(MJ)
Total	3.20E+02	0.00E+00	3.20E+02	1.46E+03	0.00E+00	1.46E+03	0.00E+00	0.00E+00	0.00E+00	0.00E+00	4.1E+01
A1- A3	1.69E+02	0.00E+00	1.69E+02	1.32E+03	0.00E+00	1.32E+03	0.00E+00	0.00E+00	0.00E+00	0.00E+00	3.7E+01
A4	1.28E-01	0.00E+00	1.28E-01	5.25E+01	0.00E+00	5.25E+01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	3E-01
A5	4.61E-03	0.00E+00	4.61E-03	8.15E-01	0.00E+00	8.15E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	9.0E-03
B1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.0E+00
B2	1.51E+02	0.00E+00	1.51E+02	7.33E+01	0.00E+00	7.33E+01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	3.0E+00
B3	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.0E+00
B4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.0E+00
B5	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.0E+00
B6	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.0E+00
B7	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.0E+00
C1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.0E+00
C2	1.27E-02	0.00E+00	1.27E-02	5.98E+00	0.00E+00	5.98E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	2.9E-02
C3	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.0E+00
C4	6.13E-02	0.00E+00	6.13E-02	8.01E+00	0.00E+00	8.01E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.2E-01

Output Flows and Waste Categories								
Module	HWD	NHWD	HLRW	ILLRW	CRU	MFR	MER	EE
	(kg)	(kg)	(kg)	(kg)	(kg)	(kg)	(kg)	(MJ)
Total	0.00E+00	3.65E+01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
A1- A3	0.00E+00	7.37E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
A4	0.00E+00	6.41E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
A5	0.00E+00	3.64E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B2	0.00E+00	8.30E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B3	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B5	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B6	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B7	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C2	0.00E+00	5.51E-03	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C3	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C4	0.00E+00	2.46E+01	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Greenhouse Gas Emissions and Removals								
Module	BCRP	BCEP	BCRK	BCEK	BCEW	CCE	CCR	CWNR
	(kg CO2e)	(kg CO2e)	(kg CO2e)	(kgCO2e)	(kg CO2e)	(kg CO2e)	(kg CO2e)	(kg CO2e)
Total	0.00E+00	0.00E+00	2.44E+00	2.44E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
A1- A3	0.00E+00	0.00E+00	2.44E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
A4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
A5	0.00E+00	0.00E+00	0.00E+00	2.44E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B2	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B3	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B5	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B6	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
B7	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C2	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C3	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
C4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

### Interpretation

Due to the high degree of value add within the vikrell product manufacturing process, the Kohler raw material life cycle stage drives most of the environmental impact categories for SMC (Sheet Modling Compound) ware.

Raw material impacts are mainly driven by the polymeric resins in the SMC body. Therefore, projects that improve product design and material choices have been and will continue to be a primary area of focus. Hardware accessories, especially those that contain metals such as brass and steel, also carry a greater contribution toward overall product environmental impact. Mass reduction and material substitution are areas of focus within the supplier operations portion of the product life cycle.

Where applicable, water use reduction efforts will see the greatest return on investment due primarily to the associated reduction in energy required to pump and treat this water. These efforts must be balanced against the product and product system's capacity to operate effectively when less water is available as a motive force.

### ADDITIONAL INFORMATION, EVIDENCE AND TEST RESULTS

Formaldehyde testing is performed using UL Environment's GREENGUARD test method following the requirements of GREENGUARD certification program incorporating ASTM standard D 6670, ASTM Standard D 5116 and United States Environmental Protection Agency's (US EPA) ETV Office Furniture Protocol.

## REFERENCES

- PCR Part A           UL Environment and Institut Bauen und Umwelt e.V., Königswinter (pub.): Product Category Rules for Construction Products from the range of Environmental Product Declarations of Institut Bauen und Umwelt (IBU), Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report. December 2017, version 3
- PCR Part B           UL Environment and Institut Bauen und Umwelt e.V. (IBU). Product Category Rules Part B: Plumbing Vessel EPD Requirements (V1, January 2018)
- ISO 14025            ISO 14025:2011-10, Environmental labels and declarations — Type III environmental declarations — Principles and procedures.
- ISO 14040            ISO 14040:2009-11, Environmental management — Life cycle assessment — Principles and framework
- ISO 14044            ISO 14044:2006-10, Environmental management — Life cycle assessment — Requirements and guidelines
- ISO 21930            Sustainability in buildings and civil engineering works — Core rules for environmental product declarations of construction products and services
- EN 15804            EN 15804:2012-04: Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction product
- WaterSense®        US EPA, Office of Wastewater Management <http://www.epa.gov/watersense>
- ULE 2013            UL Environment, General Program Instructions, 2013.
- OHSAS 18001        Occupational Health and Safety Management Systems - Requirements
- ISO 14001            Environmental Management Systems - Requirements with guidance for use
- ASME A112.19.2/CSA B45.1    Ceramic Plumbing Fixtures
- ADA                 Americans with Disabilities Act - Standards for Accessible Design
- ICC/ANSI A117.1    International Code Council - Accessible and Usable Buildings and Facilities
- CSA B651            Accessible Design for Built Environment
- OBC                 Ontario Building Code Section 3.8 - Barrier-Free Design
- ICES-003            Industry Canada, Interference Causing Equipment Standard 003 - Information Technology Equipment (ITE) - Limits and methods of measurement
- FCC part 15         Federal Communications Commission, Title 47, Part 15 - Radio Frequency Devices
- DOE-Energy Policy Act 1992    Department of Energy - Energy Policy Act 1992
- ASME A112.19.14         Six Liter Closets Equipped with a Dual Flushing Device
- ADA-Children's Environment    ADA Standards for Accessible Design - Clause 604.9
- ASME A112.19.19-06         Vitreous China Nonwater Urinals
- GREENGUARD        UL Environment, <http://greenguard.org/en/index.aspx>