

MARINE GENERATOR SPECIFICATIONS



KOHLER[®]
IN POWER. SINCE 1920.

Generator Model	kW*	Hz	Cylinder	RPM	Phase	Voltage		Amps		Length x Width x Height mm (in) H – Housed / U – Unhoused	Weight (Wet) kg (lb)
6EKOD	6	60	3	1800	1	120	50	H – 780 (30.7) x 528 (20.8) x 559 (22)	H – 222 (489)		
						120 / 240	50 / 25				
5EFKOD	5	50	3	1500	1	115 / 230	43.4 / 21.7	U – 743 (29.3) x 448 (17.6) x 536 (21.1)	U – 185 (407)		
						230	21.7				
						240	20.8				
9EKOZD	8.5	60	3	1800	1	120	70.8	H – 865 (34.1) x 528 (20.8) x 559 (22)	H – 249 (548)		
						120 / 240	70.8 / 35.4				
7EFKOZD	7	50	3	1500	1	115 / 230	60.8 / 30.4	U – 827 (32.6) x 448 (17.6) x 536 (21.1)	U – 211 (465)		
						230	30.4				
						240	29.2				
11EKOZD	11	60	4	1800	1	120	91.7	H – 960 (37.8) x 528 (20.8) x 559 (22)	H – 279 (616)		
						120 / 240	91.7 / 45.8				
9EFKOZD	9	50	4	1500	1	115 / 230	78.3 / 39.1	U – 922 (36.3) x 448 (17.6) x 536 (21.1)	U – 241 (532)		
						230	39.1				
						240	37.5				
11EKOZD	11	60	4	1800	3	220 / 380	20.9	H – 960 (37.8) x 528 (20.8) x 559 (22)	H – 406 (896)		
						240 / 416	19.1				
9EFKOZD	9	50	4	1500	3	120 / 240	33.1	U – 922 (36.3) x 448 (17.6) x 536 (21.1)	U – 376 (830)		
						127 / 220	36.1				
						230 / 400	16.2				
14EKOZD	14	60	3	1800	1	120	117	H – 1064 (41.9) x 652.5 (25.7) x 711 (27.9)	H – 395 (870)		
						120 / 240	59				
12EFKOZD	12	50	3	1500	1	230	53	U – 984 (38.8) x 580 (22.8) x 695 (27.4)	U – 376 (830)		
						240	40				
						120 / 208	49				
14EKOZD	14	60	3	1800	3	120 / 240	43	H – 1064 (41.9) x 652.5 (25.7) x 711 (27.9)	H – 406 (896)		
						120 / 240	59				
						127 / 220	46				
						139 / 240	43				
12EFKOZD	12	50	3	1500	3	277 / 480	22	U – 984 (38.8) x 580 (22.8) x 695 (27.4)	U – 376 (830)		
						110 / 190	46				
						115 / 230	38				
						115 / 230	53				
						120 / 208	42				
16EKOZD	16	60	3	1800	1	230 / 400	22	H – 1064 (41.9) x 652.5 (25.7) x 711 (27.9)	H – 406 (896)		
						240 / 416	21				
						220 / 380	23				
						120 / 208	56				
						120 / 240	49				
13.5EFKOZD	14	50	3	1500	1	120 / 240	67	U – 1003 (39.5) x 580 (22.8) x 695 (27.4)	U – 376 (830)		
						230	59				
16EKOZD	16	60	3	1800	3	240	40	H – 1064 (41.9) x 652.5 (25.7) x 711 (27.9)	H – 406 (896)		
						120 / 240	67				
						127 / 220	53				
						139 / 240	49				
						277 / 480	25				
13.5EFKOZD	13.5	50	3	1500	3	110 / 190	52	U – 1003 (39.5) x 580 (22.8) x 695 (27.4)	U – 376 (830)		
						115 / 230	43				
						115 / 230	59				
						120 / 208	47				
						230 / 400	25				
21EKOZD	21 / 21	60	4	1800	1	240 / 416	24	H – 1197 (47.12) x 652.5 (25.69) x 711 (27.99)	H – 480 (1059)		
	21 / 21					88					
18EFKOZD	18 / 18	50	4	1500	1	220 / 380	26	U – 1121 (44.13) x 577.5 (22.74) x 694 (27.31)	U – 440 (970)		
	14.5 / 14.5					61					

Generator Model	kW*	Hz	Cylinder	RPM	Phase	Voltage		Amps		Length x Width x Height mm (in) H – Housed / U – Unhoused	Weight (Wet) kg (lb)
21EKOZD	21	60	4	1800	3	120 / 208	73	H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9)	H – 480 (1059)		
						120 / 240	64				
						120 / 240	80				
17EFKOZD	17	50	4	1500	3	127 / 220	69	U – 1121 (44.1) x 577.5 (22.7) x 694 (27.3)	U – 440 (970)		
						139 / 240	64				
						277 / 480	32				
						110 / 190	65				
						115 / 230	54				
						115 / 230	70				
24EKOZD	24	60	4	1800	1	120 / 208	58	H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9)	H – 489 (1078)		
						230 / 400	31				
						240 / 416	29				
20.5EFKOZD	21	50	4	1500	3	220 / 380	33	U – 1138 (44.8) x 577.5 (22.7) x 694 (27.3)	U – 449 (990)		
						240	78				
						230	90				
24EKOZD	24	60	4	1800	3	120	200	H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9)	H – 489 (1078)		
						120 / 240	100				
						230	90				
						240	78				
						120 / 208	84				
20.5EFKOZD	20.5	50	4	1500	3	120 / 240	73	H – 1197 (47.1) x 652.5 (25.7) x 711 (27.9)	H – 489 (1078)		
						120 / 240	92				
						127 / 220	79				
						139 / 240	73				
						277 / 480	37				
32EKOZD	32	60	4	1800	1	110 / 190	78	H – 1303 (51.30) x 661 (26.04) x 778 (30.64)	H – 607 (1339)		
						115 / 230	65				
						115 / 230	85				
						120 / 208	72				
						230 / 400	37				
28EFKOZD	28	50	4	1500	3	240 / 416	36	U – 1222 (48.13) x 643 (25.33) x 733 (28.86)	U – 531 (1170)		
						220 / 380	39				
						120 / 240	133				
						120 / 208	111				
						120 / 240	96				
						120 / 240	142				
						127 / 220	105				
						139 / 240	96				
277 / 480	48										
40EKOZD	40	60	4	1800	1	230	122	H – 1354 (53.31) x 661 (26.04) x 778 (30.64)	H – 637 (1404)		
						240	96				
						110 / 190	106				
						110 / 220	92				
						115 / 230	117				
						120 / 208	97				
						230 / 400	51				
						240 / 416	49				
220 / 380	53										
35EFKOZD	35	50	4	1500	3	120 / 240	152	U – 1274 (50.17) x 643 (25.33) x 733 (28.86)	U – 567 (1250)		
						120 / 208	139				
						120 / 240	120				
						120 / 240	142				
						127 / 220	131				
						139 / 240	120				
						277 / 480	60				
						230	152				
						240	133				
						110 / 190	129				
110 / 220	112										
115 / 230	130										
120 / 208	121										
230 / 400	63										
240 / 416	61										
220 / 380	65										

*kW rating varies by voltage. Consult the generator spec sheet for more detail.

Generator Model	kW*	Hz	Cylinder	RPM	Phase	Voltage	Amps	Length x Width x Height mm (in)			Weight (Wet) kg (lb)
								H – Housed / U – Unhoused / R – Radiator			
33EFOZDJ	33	50	4	1500	3	110 / 190	125	H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1524 (60) x 722 (28.4) x 960 (37.8) R – 1858 (73.2) x 827 (32.6) x 1265 (49.8)	H – 1025 (2260) U – 935 (2060) R – 957 (2110)*		
					1	115 / 230	143				
					3	220 / 380	63				
40EFOZDJ	40	50	4	1500	3	110 / 190	152	H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H – 1080 (2380) U – 971 (2140) R – 993 (2190)*		
					1	115 / 230	174				
					3	220 / 380	76				
50EFOZDJ	50	50	4	1500	3	110 / 190	190	H – 1690 (66.5) x 767 (30.2) x 1015 (39.9) U – 1606 (63.2) x 738 (29) x 961 (37.8) R – 1941 (76.4) x 827 (32.5) x 1265 (49.8)	H – 1114 (2456) U – 1005 (2216) R – 1028 (2266)*		
					1	115 / 230	196				
					3	220 / 380	95				
55EOZDJ	55	60	4	1800	3	120 / 208	191	H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H – 1090 (2404) U – 982 (2164) R – 1004 (2214)*		
					1	120 / 240	221				
					3	120 / 240	180				
45EFOZDJ	45	50	4	1500	3	110 / 190	171	H – 1633 (64.3) x 767 (30.2) x 1015 (39.9) U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H – 1090 (2404) U – 982 (2164) R – 1004 (2214)*		
					1	110 / 220	148				
					3	220 / 380	96				
65EOZDJ	65	60	4	1800	3	120 / 208	226	H – 1690 (66.5) x 767 (30.2) x 1015 (39.9) U – 1606 (63.2) x 738 (29) x 961 (37.8) R – 1941 (76.4) x 827 (32.5) x 1265 (49.8)	H – 1125 (2480) U – 1016 (2240) R – 1039 (2290)*		
					1	120 / 240	221				
					3	120 / 240	213				
55EFOZDJ	55	50	4	1500	3	110 / 190	209	H – 1690 (66.5) x 767 (30.2) x 1015 (39.9) U – 1606 (63.2) x 738 (29) x 961 (37.8) R – 1941 (76.4) x 827 (32.5) x 1265 (49.8)	H – 1125 (2480) U – 1016 (2240) R – 1039 (2290)*		
					1	110 / 220	181				
					3	220 / 380	105				
80EOZDJ	80	60	4	1800	3	120 / 208	278	H – 1754 (69) x 831 (32.7) x 1032 (40.6) U – 1657 (65.2) x 753 (29.6) x 999 (39.3) R – 1992 (78.4) x 890 (35) x 1277 (50.2)	H – 1270 (2800) U – 1148 (2530) R – 1179 (2600)*		
					1	120 / 240	241				
					3	120 / 240	262				
70EFOZDJ	70	50	4	1500	3	110 / 190	266	H – 1754 (69) x 831 (32.7) x 1032 (40.6) U – 1657 (65.2) x 753 (29.6) x 999 (39.3) R – 1992 (78.4) x 890 (35) x 1277 (50.2)	H – 1270 (2800) U – 1148 (2530) R – 1179 (2600)*		
					1	110 / 220	230				
					3	220 / 380	133				
99EOZDJ	99	60	4	1800	3	120 / 208	343	H – 1829 (72) x 831 (32.7) x 1032 (40.6) U – 1732 (68.2) x 753 (29.6) x 999 (39.3) R – 2067 (81.3) x 890 (35) x 1277 (50.2)	H – 1356 (2990) U – 1243 (2740) R – 1275 (2810)*		
					1	120 / 240	298				
					3	120 / 240	325				
80EFOZDJ	80	50	4	1500	3	110 / 190	304	H – 1829 (72) x 831 (32.7) x 1032 (40.6) U – 1732 (68.2) x 753 (29.6) x 999 (39.3) R – 2067 (81.3) x 890 (35) x 1277 (50.2)	H – 1356 (2990) U – 1243 (2740) R – 1275 (2810)*		
					1	110 / 220	262				
					3	220 / 380	152				
125EOZDJ	125	60	6	1800	3	120 / 208	434	H – 2205 (86.8) x 971 (38.2) x 1065 (41.9) U – 2068 (81.4) x 893 (35.2) x 1003 (39.5) R – 2466 (97.1) x 1129 (44.5) x 1275 (50.2)	H – 1683 (3710) U – 1515 (3340) R – 1578 (3478)		
					1	120 / 240	376				
					3	120 / 240	410				
100EFOZDJ	100	50	6	1500	3	110 / 190	380	H – 2205 (86.8) x 971 (38.2) x 1065 (41.9) U – 2068 (81.4) x 893 (35.2) x 1003 (39.5) R – 2466 (97.1) x 1129 (44.5) x 1275 (50.2)	H – 1683 (3710) U – 1515 (3340) R – 1578 (3478)		
					1	110 / 220	328				
					3	220 / 380	190				
150EOZDJ	150	60	6	1800	3	120 / 208	520	H – 2205 (86.8) x 971 (38.2) x 1065 (41.9) U – 2091 (82.3) x 893 (35.2) x 1003 (39.5) R – 2498 (98) x 1129 (44.5) x 1275 (50.2)	H – 1719 (3789) U – 1551 (3419) R – 1613 (3557)		
					1	120 / 240	451				
					3	120 / 240	492				
125EFOZDJ	125	50	6	1500	3	110 / 190	474	H – 2205 (86.8) x 971 (38.2) x 1065 (41.9) U – 2091 (82.3) x 893 (35.2) x 1003 (39.5) R – 2498 (98) x 1129 (44.5) x 1275 (50.2)	H – 1719 (3789) U – 1551 (3419) R – 1613 (3557)		
					1	120 / 208	433				
					3	110 / 220	409				
200EOZDJ	200	60	6	1800	3	120 / 208	694	H – 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U – 2490 (98) x 970 (38.2) x 1086 (42.8)	H – 2147 (4733) U – 2067 (4558)		
					1	120 / 240	601				
					3	120 / 240	656				
175EFOZDJ	175	50	6	1500	3	110 / 190	665	H – 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U – 2490 (98) x 970 (38.2) x 1086 (42.8)	H – 2147 (4733) U – 2067 (4558)		
					1	110 / 220	574				
					3	120 / 208	607				

*kW rating varies by voltage. Consult the generator spec sheet for more detail.

AMERICAS/CARIBBEAN
+1 920-565-3381
+1 800-544-2444
Fax 920-459-1646

CHINA
+86 21 26062169
+86 400 1808 900

**EUROPE
MIDDLE EAST
AFRICA**
+31 168 331630

ASIA PACIFIC
+65 6264 6422
Fax +65 6264 6455

INDIA
+91 80 42867000
Fax +91 80 23615972

**New Zealand
Australia**
+61 88 29 02100

KOHLERPOWER.COM

Printed in U.S.A. G12-479 7/18 © 2018 by Kohler Co.