

TOILET

PERFORMANCE



STERLING
A KOHLER COMPANY

THE BOLD LOOK
OF **KOHLER**®

COMPARISON

No one knows toilets quite like Kohler. For over 140 years, Kohler has built a proud legacy of craftsmanship and innovation as we pushed the limits of design, style and technology. Our award-winning toilets are easy to install, proven to last and built to impress. And, together with Sterling, a Kohler company, we firmly stand behind the toilets we manufacture.



	Windham	Stinson
Brand	STERLING	STERLING
Flushing System	Flapper	Flapper
Rough-In	10" / 12" / 14"	12"
Toilet Type	Two-Piece	Two-Piece
Bowl Height	Standard / Luxury Height	Standard / Luxury Height
Bowl Shape	Round-Front / Elongated	Elongated
Tank/Bowl Connection	Encapsulated Three-Bolt Installation	Encapsulated Three-Bolt Installation
Gallons Per Flush (GPF)	1.28 / 1.6	1.28 / 1.6
Trapway	Exposed	Exposed
Touchless Models Available		



Wellworth	Highline	Cimarron
KOHLER	KOHLER	KOHLER
Canister / Dual-Flush	Canister / Dual-Flush	AquaPiston
12" / 14"	10" / 12" / 14"	10" / 12" / 14"
Two-Piece	Two-Piece	One-Piece / Two-Piece
Standard	Comfort Height	Comfort Height
Round-Front / Elongated	Round-Front / Elongated	Round-Front / Elongated
Encapsulated Three-Bolt Installation	Encapsulated Three-Bolt Installation	DryLock Installation
1.1 or 1.6 / 1.28 / 1.6	1.0 / 1.1 or 1.6 / 1.28 / 1.6	1.28 / 1.6
Exposed	Exposed / Concealed	Exposed / Concealed / Skirted
		•

PRODUCT ATTRIBUTES

BOWL HEIGHTS



Less than 17"

Standard Height

Traditional height toilets are ideal for many users



17"-19"

Luxury Height® and Comfort Height®.
Make standing and sitting easier

BOWL SHAPES



Over 28½"

Elongated Bowl

Provides added room and comfort for seating



As small as 25¼"

Round-Front Bowl

A good solution for small spaces

TRAPWAY STYLES



Exposed Trapway

Traditionally designed, exposed trapways can be seen from the side of the toilet



Concealed Trapway

Features a smooth trapway surface that's easy to wipe clean



Skirted Trapway

Offers an easy-to-clean, smooth surface from front to back

ROUGH-IN



Most bathrooms have a standard 12" rough-in (the measurement between the wall and outlet pipe). We also offer 10" and 14" options.

WATERSENSE®



WaterSense-labeled toilets meet strict EPA flushing guidelines, including using at least 20 percent less water than 1.6-gallon toilets.

INNOVATIVE TECHNOLOGIES

FLOOR SAVER®



Available on select STERLING® toilets, the Floor Saver footprint helps cover marks left by many two-piece toilets.

PRO FORCE® TECHNOLOGY



STERLING toilets with Pro Force technology feature a powerful siphonic suction action, sending 100 percent of the water through the rim for superior waste removal and bowl cleanliness.

THREE-BOLT INSTALLATION



Three encapsulated pre-installed bolts save installation time and provide more options for adjustment.

DRYLOCK™



The KOHLER® DryLock Fast Install System makes no-leak installations fast and foolproof. It requires only a socket wrench to secure the tank to the bowl and eliminates bolt holes drilled into the tank.

DUAL-FLUSH



An innovative trip lever combines water savings with a powerful flush by offering the choice of 1.1 or 1.6 gallons per flush.

CLEAN CAPS®



Available on KOHLER concealed trapway toilets—also available as a kit—Clean Caps low-profile bolt caps make it easier to keep the toilet clean.

READYLOCK™



We make it easy to install a skirted toilet. Our innovative installation system doesn't require drilling, caulk or special tools.

TOUCHLESS TECHNOLOGY



The no-touch flush means fewer germs to pick up or leave behind. Or add a touchless flush kit to bring a no-touch flush to most toilets.

WINDHAM™

Windham toilets are engineered to deliver exceptional performance and designed for functionality and style.

Proven Flushing Performance

Proven 800–1,000 gram one-flush cleansing performance guarantee

Fully Glazed Trapway

A fully glazed trapway helps ensure a strong, complete flush to reduce plugging

Pro Force® Technology

Pro Force technology creates a powerful siphonic suction action, sending 100 percent of the water through the rim for superior waste removal and bowl cleanliness

Save Water Without Sacrificing Performance

High-efficiency toilets (HET) pack a powerful flush and can save up to 16,500 gallons of water each year versus a 3.5 gpf toilet*

Easy Three-Bolt Installation

Three pre-installed encapsulated bolts save installation time and provide more options for adjustment



PRO FORCE
TECHNOLOGY



THREE-BOLT
INSTALLATION

*Based on a household of four, each flushing 5.1 times per day, 365 days per year.

SKU	Tank SKU	Bowl SKU	Bowl Shape	Rough-In	GPF	ADA	Right-Hand Trip Lever Option
403081	404551	403215	Elongated	12"	1.28 		
403082	404551	403315	Elongated	12"	1.28 	•	•
403080	404551	403015	Round-Front	12"	1.28 		
402315	404515	403315	Elongated	12"	1.6	•	•
402215	404515	403215	Elongated	12"	1.6		
402015	404515	403015	Round-Front	12"	1.6		
402079	404544	403215	Elongated	14"	1.28 		
402078	404544	403015	Round-Front	14"	1.28 		
402210	404515	404210	Elongated	10"	1.6		

To learn more about WaterSense®-labeled toilets, visit [EPA.gov/WaterSense](https://www.epa.gov/WaterSense).

STINSON®

With an efficient, powerful flush, the Stinson toilet delivers consistency and understated elegance.

Proven Flushing Performance

Proven 1000 gram one-flush cleansing performance guarantee

Fully Glazed Trapway

A fully glazed trapway helps ensure a strong, complete flush to reduce plugging

Pro Force® Technology

Pro Force technology creates a powerful siphonic suction action, sending 100 percent of the water through the rim for superior waste removal and bowl cleanliness

Floor Saver® Footprint

The Floor Saver footprint helps cover the old footprint left by many two-piece toilets

Easy Three-Bolt Installation

Three pre-installed encapsulated bolts save installation time and provide more options for adjustment



FLOOR SAVER FOOTPRINT



PRO FORCE TECHNOLOGY



THREE-BOLT INSTALLATION

SKU	Tank SKU	Bowl SKU	Bowl Shape	Rough-In	GPF	ADA	Right-Hand Trip Lever Option
402076	402091	403070	Elongated	12"	1.28 		
402077	402091	403370	Elongated	12"	1.28 	•	•
402075	402071	403070	Elongated	12"	1.6		
402375	402071	403370	Elongated	12"	1.6	•	•

To learn more about WaterSense®-labeled toilets, visit [EPA.gov/WaterSense](https://www.epa.gov/watersense).

WELLWORTH® / HIGHLINE®

Designed for the professional plumber, we offer a variety of rough-in, water usage and height options to meet every installation need.

Maximum Power

Flushing technology provides 1,000 grams of bulk-waste removal

Plug-Free Clean

The water delivery of the flush is precision-designed to make the toilet virtually plug-free

Easy to Service

A universal replacement gasket fits all KOHLER® canister flush valve toilets. The gasket takes seconds to replace and doesn't require multiple replacement parts

Cleaner Bowl

The powerful flush sends water rushing to the rim and bowl from all sides—resulting in a cleaner bowl



WELLWORTH

SKU	Tank SKU	Bowl SKU	Bowl Shape	Rough-In	GPF	ADA	Right-Hand Trip Lever Option	Insuliner* Option	Additional Features
K-3988	K-4458	K-4198	Elongated	12"	1.1 / 1.6 		•		
K-3987	K-4458	K-4197	Round-Front	12"	1.1 / 1.6 		•		
K-3998	K-4467	K-4198	Elongated	12"	1.28 		•	•	
K-3997	K-4467	K-4197	Round-Front	12"	1.28 		•	•	
K-3978	K-4468	K-4198	Elongated	12"	1.6		•		
K-3977	K-4468	K-4197	Round-Front	12"	1.6		•		
K-3948	K-4841	K-4198	Elongated	14"	1.28 		•	•	
K-3947	K-4841	K-4197	Round-Front	14"	1.28 		•	•	

To learn more about WaterSense®-labeled toilets, visit EPA.gov/WaterSense.

*Insuliner® tank liner minimizes condensation on the tank when exposed to high humidity.

No Flapper. No Leaks. No Problem.

The canister flush valve harnesses the force of gravity to send 360 degrees of water rushing into the system—increasing the power and effectiveness of the flush

Three-Bolt Installation

Three encapsulated pre-installed bolts save installation time and provide more options for adjustment

Ideal Retrofit Footprint

Great for remodeling, the toilet base is large enough to cover most existing toilet footprints

Dual-Flush


Dual-flush models feature an innovative trip lever that combines water savings with a powerful flush by offering the choice of 1.1 or 1.6 gallons per flush

Easy to Clean

The one-piece design, concealed trapway and Clean Caps®—our low-profile toilet floor bolt caps—make it easy to keep the toilet clean (available exclusively on K-76301)

Comfort Height® Bowl

All Highline toilets feature a taller bowl height which makes sitting and standing easier



THREE-BOLT INSTALLATION



DUAL-FLUSH



CLEAN CAPS

HIGHLINE

SKU	Tank SKU	Bowl SKU	Bowl Shape	Rough-In	GPF	ADA	Right-Hand Trip Lever Option	Insuliner* Option	Additional Features
K-5298	K-5308	K-5297	Elongated	12"	1.0	•	•		
K-3989	K-4458	K-4199	Elongated	12"	1.1 / 1.6	•	•		
K-76301	K-5311	K-80020	Elongated	12"	1.28	•	•		Concealed Trapway, Clean Caps
K-3999	K-4467	K-4199	Elongated	12"	1.28	•	•	•	
K-5481	K-4467	K-5393	Round-Front	12"	1.28	•	•		
K-3979	K-4468	K-4199	Elongated	12"	1.6	•	•		
K-3949	K-4841	K-4199	Elongated	14"	1.28	•	•	•	
K-6393	K-4458	K-4373	Elongated	10"	1.1 / 1.6	•	•		
K-3889	K-4467	K-4373	Elongated	10"	1.28	•	•	•	

To learn more about WaterSense®-labeled toilets, visit EPA.gov/WaterSense.

*Insuliner® tank liner minimizes condensation on the tank when exposed to high humidity.

CIMARRON®

With a clean, versatile look, the Cimarron toilet combines flushing performance with graceful curves.

Smarter Power

Flushes 4x more than the average adult needs

Comfort Height® Bowl

Taller bowl height makes sitting and standing easier

DryLock™ Fast Install System

The DryLock Fast Install System makes no-leak installations fast and foolproof—requiring only a socket wrench to secure the tank to the bowl and eliminating bolt holes drilled into the tank

Easy to Clean

The one-piece design, concealed trapway and Clean Caps®—our low-profile toilet floor bolt caps—make it easy to keep the toilet clean (available exclusively on K-3619)

ReadyLock™ Installation System

The ReadyLock installation system is a simple solution for skirted toilets that saves time, hassle and eliminates the need to drill into the floor for a standard 12-inch rough-in (available exclusively on K-5310)

Touchless Technology

Models that feature a no-touch flush mean fewer germs to pick up or leave behind. Or add a Touchless flush kit to bring a no-touch flush to most toilets (available exclusively on K-6418 and K-6419)



DRYLOCK



CLEAN CAPS



READYLOCK



TOUCHLESS TECHNOLOGY

SKU	Tank SKU	Bowl SKU	Bowl Shape	Rough-In	GPF	ADA	Right-Hand Trip Lever Option	Insuliner* Option	Additional Features
One-Piece Toilets									
K-3619			Elongated	12"	1.28 	•	•		Concealed Trapway, Clean Caps
K-3828			Elongated	12"	1.28 	•	•		
Two-Piece Toilets									
K-5310	K-4369	K-5309	Elongated	10" / 12" / 14"†	1.28 	•	•		Skirted Trapway, ReadyLock
K-3609	K-4421	K-4309	Elongated	12"	1.28 	•	•	•	
K-6418	K-5692	K-4309	Elongated	12"	1.28 				Touchless Technology
K-3887	K-4166	K-4347	Round-Front	12"	1.28 		•	•	
K-6419	K-5693	K-4347	Round-Front	12"	1.28 				Touchless Technology
K-3589	K-4418	K-4309	Elongated	12"	1.6	•	•		
K-3888	K-4167	K-4347	Round-Front	12"	1.6		•		
K-3851	K-4166	K-4829	Round-Front	10"	1.28 		•	•	

*Insuliner, tank liner minimizes condensation on the tank when exposed to high humidity.

† 10" and 14" rough-in require kit (sold separately).

To learn more about WaterSense®-labeled toilets, visit EPA.gov/WaterSense.

AQUAPISTON®

A patented flush engine from Kohler, AquaPiston delivers high-octane power for our toilets.

Maximum Power

A 3-to-2 ratio between the AquaPiston inlet and outlet valve harnesses the force of gravity to send water rushing into the bowl from all sides—delivering maximum power

Canister Design

The AquaPiston design and seal eliminate leakage problems commonly associated with traditional rubber flappers

Universal Gasket

Fits all KOHLER® canister flush valve toilets, making replacement a snap, and it has 90 percent less exposed seal material than a 3" flapper



AQUAPISTON FLUSHING TECHNOLOGY



	AquaPiston	Flappers
Water Intake	360 degrees	< 360 degrees
Inlet/Outlet Ratio	3:2	1:1
Flush Actuating Force	2.2 lb	Approximately 5 lb
Exposed Seal Material	90% less than 3" flappers	N/A
Serviceability	Patented canister with universal gasket is easy to service.	Flappers are not universal and are model specific.

us.KOHLER.com
SterlingPlumbing.com



THE BOLD LOOK
OF **KOHLER**®

Form 16-2121-0417
© 2017 Kohler Co.
Kohler, Wisconsin 53044
Printed in U.S.A.
1-800-4-KOHLER
(1-800-456-4537)